

YardBright™

Landscape Power Unit

MODEL NO: GBTPS-60-12DW

INPUT: 120VAC 60Hz 2A

OUTPUT: 12VDC 5.0A



Intertek

3106676

CONFORMS TO UL STD 1838
CERTIFIED TO CSA STD
C22.2 No. 250.7

On Auto 2H 4H 6H 8H



Test Error



Sensor



Timer Setting



CAN ICES-3 (B)/NMB-3(B)

SUITABLE FOR OUTDOOR USE ONLY. NOT FOR USE WITH DIMMERS. TOTAL BULB USAGE NOT TO EXCEED 60WATTS MAX. MOUNT AT LEAST 1 FEET (30cm) ABOVE GROUND

MADE IN CHINA
FABRIQUE EN CHINE

GBTPS-60-12DW

INSTRUCTIONS

This sleek new small transformer is specifically designed for use with Leds. It's ideal for Led lighting systems, submersible fixtures and submersible pumps. Features include On, Dusk to Dawn, 2, 4, 6 & 8 hours. Integrated photocell automatically turns the unit on at dusk and counts down according to your hour setting. It is designed to be used with 12V AC/DC and 12VDC Leds.

On = On at all times

Auto = Dusk to Dawn operation

2H = Two hours of operation after unit turns on

4H = Four hours of operation after unit turns on

6H = Six hours of operation after unit turns on

8H = Eight hours of operation after unit turns on

Test = You can put the unit in test mode including the photocell

Error = The unit is overloaded, or has a short in the installation. It will automatically reset when the problem is corrected.

Timer Setting = Use this button to switch all of the settings above.

Input: 120VAC 60Hz 2A

Output: 12VDC 5.0A

Height: 4.25 Inches

Width: 4.25 Inches

Depth: 2.00 Inches

Power cord: 5ft. long

Suitable for outdoor use only. Not for use with dimmers on the 120VAC side. Can be used with 12VDC dimmers on the 12VDC output side. Total bulb usage not to exceed 60 Watts.

5 Year Warranty